

FERRI®

www.ferri-america.com



Hydraulic block tap for transport with manual activation (no chains or holders).












Mechanical block pin for transport (no chains or holders).



ZMT

Offset in-line slope mowers

• Agriculture • Green areas • Tractors from 50 to 80 HP

ZMT 1600	 50 to 60 HP	 5'4"	 7'3"
ZMT 1800	 60 to 70 HP	 6'0"	 7'11"
ZMT 2000	 70 to 80 HP	 6'8"	 8'7"

Distributed by: J. S. Woodhouse Co., Inc.
1314 Union St
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com



Offset in-line slope mowers

• Agriculture • Green areas • Tractors from 50 to 80 HP



Strong points



Floating frame: the joint pin on tractor side allows the head system to follow the ground, protecting the arms structure of the parallelogram.



Hydraulic sideshift ram fitted within parallel arms for better protection during work.



Rotation joint on self-lubricating bushing.







Cable controls with floating head (optional)

Work position



		ZMT 1600	ZMT 1800	ZMT 2000
A	ft.	5'4"	6'0"	6'8"
B	ft.	7'3"	7'11"	8'7"
C	ft.	6'1"	6'4"	6'4"
D	ft.	1'10"	1'10"	1'10"
H	ft.	6'8"	6'8"	6'8"
I	ft.	4'6"	4'6"	4'6"



Equipment	MOD.	ZMT 1600	ZMT 1800	ZMT 2000
Cutting	ft	5' 4"	6' 0"	6' 8"
Power take-	rpm	540	540	540
Belt	No.	3	3	4
Tractor required power	HP	50 / 80	60 / 70	70 / 80
Rotor	rpm	2430	2510	2510
Blade tip	ft/sec	150	164	164
Weight (without PTO shaft 52,516 lbs)	lbs	1034	1298	1290
Three point linkage	Cat.	II	II	II
Minimum tractor weight	lbs	4900	5400	5800
Tractors minimum width	ft	5' 11"	6' 7"	7' 3"
 Multi-use blades. Max cut 1 1/4"	No.	40	48	48
 Hammer blades. Max cut 1 3/4"	No.	20	24	24

All data subject to change. ZM 7327 A REV.07/10/11 compiled 02/11/11 620911

Distributed by: J. S. Woodhouse Co., Inc.
1314 Union St
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com