

SUNFIRE®

HEATS UP TO 2,800 SQ. FT.


SF120
RADIANT HEATER
120,000 BTUs



LOW NOISE



ODORLESS



ZERO CO
EMISSIONS*



DUST FREE
EXPERIENCE

XTREME CLEAN™
ADVANCED TECHNOLOGY BURNER

DUAL FUEL
DIESEL/#2 KEROSENE



THERMOSTAT CONTROL OPTION
CONNECT TO STANDARD WALL THERMOSTAT
(THERMOSTAT NOT INCLUDED)

**MADE IN
USA**

* Zero CO with properly tuned burner and at steady state temperature.

THE ULTIMATE HEATING

EXPERIENCE

X-TREME CLEAN™ ADVANCED TECHNOLOGY BURNER

Advanced technology extends nozzle life, improves burn efficiency to achieve zero* carbon monoxide emissions, and includes RAPID ACCESS™ Easy Maintenance Hatch.

*Zero CO with properly tuned burner and at steady state temperature.

RAPID ACCESS™ EASY MAINTENANCE HATCH

Allows quick access to the nozzle assembly making tune-ups and maintenance ultra-fast and easy.



SPECIFICATIONS

BTU/Hr:	120,000	Weight:	115 lbs.	Thermostat Options: Use any mechanical or battery operated wall thermostat. Do not use a thermostat that requires 120V of electricity to operate. <i>Thermostat not included.</i>
Fuel:	Diesel, #2 Fuel Oil, Kerosene	Product Dimensions:	32"L x 28.5"W x 33.75"H	
Flow Rate GPH:	.87 Diesel and .78 Kerosene	Run Time:	16 Hrs. Diesel / 18 Hrs. Kerosene	
Tank Capacity:	14 Gallons	Minimum Clearances:	Front: 84" Sides: 36" Back: N/A	
Electrical Requirements:	120V 1.2 A (800 W Pure Sine INV)	<i>Keep away from combustible items.</i>		

SUNFIRE



SunFireHeaters.com