



ASM1 24" FAIRING MISTBLOWER



Technical specifications

PUMP AND CONTROL

- | | |
|--------------------|----------------------|
| • Type | Diaphragms |
| • Model | Comet APS-61 |
| • Flow rate | 62,3l/min |
| • Highest pressure | 40 bar |
| • Control | 2-ways, mechanical |
| • Pressure gauge | Glycerine 0-40 scale |

IMPELLER AND NOZZLES

- | | |
|---------------------|--------------------------|
| • Diameter | Ø610mm |
| • Propeller | 8 blades |
| • Deflector | Special fairing |
| • Gear Box | 1 speed + neutral point |
| • Highest volume | 31.400 m ³ /h |
| • Power consumption | 9,5 hp |
| • Number of nozzles | 14 |
| • Nozzle-holders | Simple with anti-drip |

TANK AND FILTER

- | | |
|-----------------------|---------------------------|
| • Capacity | 200,400 or 600 lts |
| • Self-rinsing tank | 10% out of the main tank |
| • Sanitary water tank | 15 lts |
| • Material | High density polyethylene |
| • Agitator | Hydraulic |
| • Filter | 100 lts/min |

TRACTOR REQUIREMENTS

- | | |
|---------------------------|-----------------|
| • Speed of the PTO | 540 rpm maximum |
| • Coupling to the tractor | 3 point hitch |
| • Tractor minimal power | 20 hp |



*Complements and other optional furnishings are available in this machine



www.teyme.es