

# The widest choice of quality land management attachments.





**Poly/Wire Wafers** 

# **Rotary** Brooms

Designed for use by contractors, municipalities, institutions and farmers. Hydraulically driven models for skid steers, PTO driven models for 3-pt. tractor mounts (Cat.I). 32 inch diameter convoluted brushes available in Poly (P) or both Poly and Wire (PW). All models available in 5-ft., 6-ft., & 7-ft. widths.

- Remove dirt, sand, gravel and trash from construction entrances, parking lots, bridges, driveways & sidewalks.
- Remove thatch and prepare turf for the growing season.
- Clean snow or leaves from streets, driveways, and building entrances.
- Excellent for general clean up before sealing or repairing pavement.
- Brooms angle up to 30-degrees right or left. Optional manual or hydraulic angle adjustment kits available.
- Height adjustment chains maintain an even operating position.
- Parking stand included as standard equipment.

#### **Skid Steer Rotary Broom**

- Hydraulically driven skid steer models in 5-ft., 6-ft., & 7-ft. widths with 32" diameter brushes.
- Variable flow control valve for optimum broom speed.
- Step-through mount design for easy in/out of skid steer cab.
- Optional electric solenoid hydraulic angle kit also offered.
- 4.36/1 chain drive ratio provides job matched torque to get through tough conditions.

#### 3-pt. Rotary Broom

- PTO driven 3-pt. tractor mount in 5-ft., 6-ft., & 7-ft. widths with 32" diameter brushes.
- Double gearbox drive with patented top "T-shaft" for smooth power transmission and easy reversal of brush rotation.
- Designed for Category I tractors with 1,000 lbs. or greater 3-pt. lift capacity. With bushings these models can be used on most Cat. II tractors.

## Skid Steer Rotary Broom Specifications

	SSMB-325P	SSMB-325PW	SSMB-326P	SSMB-326PW	SSMB-327P	SSMB-327PW
Overall Width (in/cm)	69 / 175	69 / 175	81 / 206	81 / 206	93 / 236	93 / 236
Brush Diameter (in/cm)	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81
Sweeping Width (in/cm)	60 / 152	60 / 152	72 / 183	72 / 183	84 / 213	84 / 213
Width @ 30° Angle (in/cm)	53 / 135	53 / 135	64 / 163	64 / 163	76 / 193	76 / 193
Mounting System	Skid Steer					
Brush Material	Poly	Poly / Wire	Poly	Poly / Wire	Poly	Poly / Wire
Hydraulic Motor Rating	16 GPM					
Oil Flow Requirement (gpm/lpm)	12-30 / 45-114	12-30 / 45-114	12-30 / 45-114	12-30 / 45-114	12-30 / 45-114	12-30 / 45-114
Dirt Deflector	Optional	Optional	Optional	Optional	Optional	Optional
Weight (lbs/kg)	640 / 290	637 / 289	740 / 336	736 / 334	840 / 381	833 / 378
Product No.	610961	610960	610966	610965	610971	610970

# 3-pt. Rotary Broom Specifications

	RMB-325P	RMB-325PW	RMB-326P	RMB-326PW	RMB-327P	RMB-327PW
Overall Width (in/cm)	69 / 175	69 / 175	81 / 206	81 / 206	93 / 236	93 / 236
Brush Diameter (in/cm)	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81
Sweeping Width (in/cm)	60 / 152	60 / 152	72 / 183	72 / 183	84 / 213	84 / 213
Width @ 30° Angle (in/cm)	53 / 135	53 / 135	64 / 163	64 / 163	76 / 193	76 / 193
Mounting System	3-pt. (Cat. I)					
Brush Material	Poly	Poly / Wire	Poly	Poly / Wire	Poly	Poly / Wire
PTO RPM Range	540	540	540	540	540	540
Dirt Deflector	Optional	Optional	Optional	Optional	Optional	Optional
Weight (lbs/kg)	720 / 326	714 / 324	780 / 354	774 / 351	840 / 381	833 / 378
Product No.	610705	610700	610755	610750	610805	610800

### **Options**

Angle Adjustments Kits (all models require either a manual or hydraulic kit)				
Product No. 610702	Manual Angle Adjustment Kit for either skid steers or 3-pt. tractor.			
Product No. 610703	3-pt. Hydraulic Angle Adjustment Kit – includes cylinder & hoses less tips.			
Product No. 610704	Skid Steer Hydraulic Angle Adjustment Kit – includes electric hydraulic solenoid control valve. For skid steer brooms used on units with only one set of remotes. Includes cylinder, hoses, valve, & flat-faced couplers. Factory installed.			
Electric Solenoid Kit (Optional)				
Product No. 610950	Field installed electric hydraulic solenoid valve kit – fits product no. #610703 hydraulic angle kit above.			

