

A necessary sprayer for recreational areas and small pasture fields



FEATURES

- 80 gallon tank with sloped sump for better drainage, 5" fillwell, and 1 $\frac{1}{4}$ " outlet.
- Gallon and liter markings on the tank.
- Agitation standard on all tanks.
- Special molded in baffling in bottom of tanks for better agitation.
- Pocket on top side of tank for extra chemical or fresh water jug.
- Rugged 12 gauge formed steel skid frame.
- Adjustable drawbar hitch and axles with 18 x 9.50 flotation tires on silver rims for trailer models.
- Lift kit to raise tongue height 3" is included.
- Electronic continuous duty motor, diaphragm pump with Viton® valves will deliver 5 GPM. Draws 9 amps at 20 PSI.
- 3.5 HP Briggs and Stratton engine with C4101 pump delivering 6 GPM at 2600 RPM and 50 PSI. 150 PSI max.
- 4 HP Honda with "Silver Cast" pump (XL4101).
- Hypro® 6 roller PTO pump (C6500D) will deliver 8 GPM at 540 RPM and 50 PSI. 150 PSI max.
- Handgun with 15' hose (380RB).
- 80" spray boom with 2 nozzles (AN1.5), 12' spray boom with 4 nozzles and spring loaded boom break away or 18' boom with 6 nozzles.
- Rear mount fits category "1" three-point.
- 3-section plumbing available for 3-section 21' boom. PTO pump required.





HOW TO ORDER Choose in this order: 1. **Model** 2. **Boom** 3. **Accessories**

	Model with Pump		
2	80 Gallon Skid with electric 5 GPM pump. Skid base is 26 ½" wide x 34" deep	9464065	138 lbs.
	80 Gallon Skid with 3.5 HP B&S engine and C4101GE pump		
	Skid base is 26 ½" wide x 34" deep	9464067	181 lbs.
	80 Gallon Skid with 4 HP Honda and "Silver Cast" pump (XL4101)		
	Skid base is 26 ½" wide x 34" deep.	9464069	181 lbs.
	80 Gallon Skid with Ace centrifugal pump and 3 HP Honda engine (1-section)	9464102	181 lbs.
	80 Gallon Skid with Ace centrifugal pump and 3 HP Honda engine (3-section)		181 lbs.
	80 Gallon Trailer with electric 5 GPM pump		202 lbs.
			245 lbs.
	80 Gallon Trailer with 4 HP Honda and "Silver Cast" pump (XL4101)		245 lbs.
	80 Gallon Trailer with Ace centrifugal pump and 3 HP Honda engine (1-section)		181 lbs.
	80 Gallon Trailer with Ace centrifugal pump and 3 HP Honda engine (3-section)		181 lbs.
	80 Gallon Rear Mount with electric 5 GPM pump		165 lbs.
	80 Gallon Rear Mount with PTO 6 roller pump for 80", 12', or 18' boom (1-section)	9464088	184 lbs.
	80 Gallon Rear Mount with PTO 6 roller pump for 21', 28', or 30' boom (3-section)		199 lbs.
	Boom with Plumbing	0-10-1000	100 100.
	<u> </u>		
	80" Boom (2 nozzles)(40" spacing)		10 lbs.
	12' Boom (4 nozzles)(40" spacing)		27 lbs.
	18' Boom (6 nozzles)(40" spacing)		38 lbs.
	21' Truss-T, Rear Cross-fold Boom (13 nozzles, spray tips not included)		85 lbs.
	28' Truss-T, Rear Cross-fold Boom (17 nozzles, spray tips not included)		110 lbs.
	30' Truss-T, Rear Cross-fold Boom (19 nozzles, spray tips not included)		115 lbs.
	Boom Extender Kit For Electric Pump (includes 2 XT020 tips)	9428147	8 lbs.
	Boom Extender Kit For Gas Engine Driven Pump (includes 2 XT020 tips)	9428149	8 lbs.
	Accessories		
	Hose Reel with 50' of 1/8" hose (less handgun)	9428114	20 lbs.
	Lawn & Turf Gun with #3 nozzle		1 lbs.


Accessories

for 40, 60, & 80 Gallon Pro Series Sprayers





9428114 25660-3 Hose Reel with 50' of ¾" hose (less handgun) Lawn & Turf Gun with #3 nozzle



Hypro® Boom X Tender

Stainless steel & Polyacetal - Flow rates = .9 - 26.3 GPM @ 30 - 60 PSI

Driven Pump (Not Pictured)

Medium Coarse Droplets

| '

Distance = 24 - 36 fee





X Te	nder Boom	Nozzles fo	or Broadcas	t Applicatio	ons
		Application Rate (GPM)			
Tip#	psi	gpm	4 mph	5 mph	6 mph
XT010	30	0.9	7	5.6	4.6
	40	1.0	7.7	6.2	5.2
	50	1.1	8.5	6.8	5.7
	60	1.2	9.3	7.4	6.2
XT020	30	1.7	12.4	9.9	8.3
	40	2.0	14.6	11.6	9.7
	50	2.2	16.0	12.8	10.7
	60	2.4	17.5	14.0	11.6

*All swaths and flow rates are based on tests conducted at 40 psi with nozzles parallel to the ground and 48-inches high while stationary.

Changes in spray height, operating pressure, mounting angle, and application speed will influence swath width.

