

FERRI®

TFC/R

FORESTRY MULCHERS FOR TRACTORS (FROM 70 TO 140 HP) (Ø max 20 cm)



Features:

Rotor with forged hammers



Frame made of structural steel

Internal counterframe made of Hardox 400

Double row of counterblades

Single transmission (with 5 belts)

Gearbox overrunning clutch

PTO shaft with torque limiter

Rear housing with hydraulic cylinder

Skids

Double front guard with chains

Technical data

Model	Width of cut m	Total width m	Weight Kg	Tractors HP/RPM	Rotor diameter mm	Total diameter rotor mm
TFC/R1600	1,60	1,80	1240	70-80/1000	420	510
TFC/R1800	1,80	2,00	1380	80-100/1000	420	510
TFC/R2000	2,00	2,20	1520	100-120/1000	420	510
TFC/R2200	2,20	2,40	1660	120-140/1000	420	510

Machines

Model
TFC/R1600
TFC/R1800
TFC/R2000
TFC/R2200

Accessories

Push over bar
Hydraulic 3-point linkage

Flails

Interchangeable on same rotor

	Forged and hardened hammers		Reinforced hammers with tungsten tips (suggested in case of rocks and stones)	
				
TFC/R1600	n° 24	Standard	n° 24	
TFC/R1800	n° 28	Standard	n° 28	
TFC/R2000	n° 32	Standard	n° 32	
TFC/R2200	n° 36	Standard	n° 36	
	Code THFZP10280		Code THFZP10280MD	

IT IS RECOMMENDED that the connection between tractor and shredder and its setting up should be made with the Dealer according to the instructions and warnings listed on our Use and Maintenance Manual. For further information please contact our after sales service.

Distributed by:
J. S. Woodhouse Co., Inc.
1314 Union St.
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com

