Technical data:	HZ-1500	HZ-2300	VHZ-2300	HG-1200	VHG-1200	HG-1200R	VHG-1200R
Opening width	1500 mm.	2300 mm.	2300 mm.	1200 mm.	1200 mm.	1200 mm.	1200 mm.
Hydraulic connections	1 double	2 double	2 double	2 double	2 double	3 double	3 double
Swing cylinder.	No	Yes	Yes	Yes	Yes	Yes	Yes
Swing radius	+ / - 45°	+ / - 43°	+ / - 43°	+ / - 43°	+ / - 43°	+ / - 43°	+ / - 43°
Pulling power on winch	None	None	3 tons	None	3 ton	None	3 ton
Wire on winch	None	None	9mm X 30m	None	9mm X 30m	None	9mm X 30m
Closing power.	2,5 ton	6 ton	6 ton	3 ton	3 ton	3 ton	3 ton
Rotator load.	None	None	None	None	None	3 ton	3 ton
Weight	132 kg.	325 kg.	420 kg.	275 kg	370 kg	275 kg.	370 kg.
Tractor power	20-50 HK.	50-100 HK.					

### **Accessories**



Hydraulic valve block For forestry tong/grapple + leveller

Option if tractor only has: 1 double acting outlet. or has: 1 single outlet and 1 back flow (max 45 L/min.) One of the handles has integrated "floating" position.

Pto shafts Forestry chains **Distance pulley** Straps Slider for cable



Distributed by:



Fransgård Maskinfabrik A/S Fredbjervej 132 9640 Farsø Denmark Tlf.+45 98632122 www.fransgard.dk

Manufacturer

HZ-1500 HZ-2300 VHZ-2300 HG-1200 VHG-1200 **HG-1200**R **VHG-1200R** 

> Grapple/tong for moving timber. Wide opening makes it easy to grip the logs. Opening width from 1200 mm to 2300 mm 1200 and 2300 models with hydraulic swing for more flexibility. R models have a hydraulic rotator on grapple turns 360° HZ-2300 & HG models have a standard 3-point hitch with storage box. VHZ & VHG models incorporates a 3-ton forestry winch on the 3-point hitch.

Fransgård Maskinfabrik A/S 9640 Farsø, Denmark www.fransgard.dk



# Fransgård

## Fransgård

### Forestry tongs for any purpose








Is the smallest forestry tong in Fransgårds wide range of forestry tongs. With a weight of only 132 kg and is it very suitable for small tractors.











The grapple will easily handle logs up to 20-30 mtr / 60/90 ft. The swing cylinder of the grapple must be connected to a float section of the tractor's hydraulic valve assembly.



All VHZ and VHG models includes a 3-ton forestry winch on the 3-point hitch, which is operated by displacing the claw to the left and is activated manually by pulling the green power cord.



HZ-2300 and HG Models have a transport box build ind the 3-point hitch. For cable slings and forestry chains etc.





VHG-1200R and HG-1200R models have a rotator and large claw mounted.

HZ-2300 and HG Models have a lower link attachment point that makes it possible to tow logs with a cable sling or a forestry chain .