



## UNIVERSAL THUMBS

For 3-Point & Subframe Backhoes , Skid-Steer Backhoes & Mini-Excavators



**UNIVERSAL THUMBS** are designed to increase the productivity and versatility of your 3-Point and Subframe Backhoes, Skid-Steer Backhoes and Mini-Excavators. Ideal for landscapers and contractors. Dig and load with the same machine. These rugged build rigid thumbs are designed to do a wide range of material handling jobs such as: land clearing, demolition, brush removal, rock, railroad tie and pipe placement, loading and unloading material. A certified welder must complete the installation.

- Thumb claws are made from T-1 high strength steel
- Two pin adjustable working positions allows for handling a wide variety of material
- Folds flat against the dipperstick for storage
- Reinforced bracing for added strength
- Thumb is shipped preassembled for ease of installation
- Mounting requires welding unit to backhoe or mini-excavator dipperstick



### SPECIFICATIONS

MODELS	UAT-50	UAT-100-R	UAT-200
For Buckets measuring from pivot pin to end of bucket teeth	Up to 17"	18" to 22"	24" to 29"
Base Mounting Plate	3-1/2" x 19"	4" x 18"	5" x 21"
Thumb Width	5"	5-1/4"	7-1/2"
Support Member	Telescopic	Telescopic	Solid
Pivot Pins	1" diameter	1" diameter	1-1/4" diameter
Weight	43 lbs.	56 lbs.	110 lbs.

**CAUTION:** When lifting heavy objects, never exceed the lift capacity of the backhoe or mini-excavator

Specifications subject to change without notice

Distributed by: J. S. Woodhouse Co., Inc.  
1314 Union St  
West Springfield, MA 01089

Phone: 413-739-5607  
Fax: 413-732-3786  
email: info@jswoodhouse.com  
website: www.jswoodhouse.com



## UNIVERSAL THUMB

*For Commercial Backhoe Loaders*



**UAT-300 UNIVERSAL THUMB** is designed to increase the productivity and versatility of your Commercial Backhoe Loader. Ideal for contractors and landscapers. Dig and load with the same machine. This extreme-duty, rigid thumb fits most commercial backhoes. Designed to do a wide range of material handling jobs from loading and unloading material, land clearing, demolition, brush removal, rock and pipe placement. A certified welder must complete the installation.

- Two pin adjustable working positions allows for handling a wide variety of material
- When not in use, thumb assembly folds flat against the dipperstick for storage or can be removed from the base plate
- Works best on buckets that measure 35" to 42" from pivot pin to the end of bucket teeth
- Thumb claws are made from T-1 high strength steel
- Thumb is shipped preassembled for ease of installation
- Mounting requires welding unit to backhoe dipperstick



### SPECIFICATIONS

MODEL	CLAW DIMENSIONS	THUMB WIDTH	MOUNTING BASE PLATE	SUPPORT ROD	PIVOT PINS	WEIGHT
UAT-300	3/4"x 6"x 38"	12"	7" x 30"	2-1/2" Dia.	2" Dia.	281 lbs.

**CAUTION:** When lifting heavy objects, never exceed the lift capacity of the backhoe or mini-excavator

*Specifications subject to change without notice*

Distributed by: J. S. Woodhouse Co., Inc.  
1314 Union St  
West Springfield, MA 01089

Phone: 413-739-5607  
Fax: 413-732-3786  
email: [info@jswoodhouse.com](mailto:info@jswoodhouse.com)  
website: [www.jswoodhouse.com](http://www.jswoodhouse.com)