



LOADER PALLET FORKS

COMPACT SERIES

4 Models, 2250 lb. Capacity



- Fits many Compact Loaders
- Class I ITA forks are forged and heat-treated
- 2250 lb. capacity/pair @ 21" load center
- Adjustable rail style forks equipped with positioning latches
- 42" useable length fork tines
- Equipped with high visibility load guard

SPECIFICATIONS

MODELS	ULF-2242	JLF-2242	SSF-2242	KLF-2242
LIFT CAPACITY	2250 lbs.	2250 lbs.	2250 lbs.	2250 lbs.
FORK LENGTH	42"	42"	42"	42"
TINE SIZE	1-1/4" x 3" Solid	1-1/4" x 3" Solid	1-1/4" x 3" Solid	1-1/4" x 3" Solid
ADJ. FORK FEATURE	Standard	Standard	Standard	Standard
LOADER FRAME DIMENSIONS	Fits many Compact Loaders that measure between 28-1/4" ID & 47-1/4" OD with 3/4" or 1" pins	Fits John Deere Compact Loaders with Quick-Change Attachment Carrier	Fits Compact Loaders with Skid Steer Style Quick Couplers	Fits Kubota Compact Loaders with Skid Steer Style Quick Couplers
FITS LOADERS PIN SIZES	3/4" or 1"	John Deere Quick Attach	Fits Skid Steer Style Quick Couplers	Fits Kubota Skid Steer Style Quick Couplers
FORK STYLE	Rail	Rail	Rail	Rail
WEIGHT	280 lbs.	280 lbs.	280 lbs.	280 lbs.

Specifications subject to change without notice



WARNING: Loader Mounted Fork attachments are specifically designed to engage and load palletized materials. Do not use forks to handle large loads such as bales, posts, etc. and avoid carrying loose or shiftable loads as they can fall or roll back onto operator causing serious injury or death.

Innovative Products Designed to Save Time & Labor

Distributed by: J. S. Woodhouse Co., Inc.
1314 Union St
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com