



Gravity Feed Chippers

The Sundown C Series gravity feed wood chippers are the ideal property management solution for homeowners, farmers, and for large property maintenance. The C series wood chippers are packed with commercial grade components such as double-sided knives, a standard chip anvil, a top discharge chip chute, and an industrial two-part urethane finish. Built rental tough, the C series gravity feed chippers are available in 3.5" and 5.5" material diameters



Model C350M

- Accepts material up to 3.5" in diameter
- Left or right chip discharge
- 2 reversible knives mounted with recessed bolts (no threaded knives)
- Easy to remove shields to access the drive components

Model C550M

- Accepts material up to 5.5" in diameter
- 360 degree chip chute rotation
- 4 reversible knives mounted with recessed bolts (no threaded knives)
- Easy to remove shields access the 3 cogged v-belt drive



SPECIFICATIONS

Models	C350M	C550M
Chip Opening	3" x 5 1/2"	5 1/2" x 8"
Drive System	PTO	PTO
Transport	3 Point Hitch	3 Point Hitch
PTO Category	Cat. 1	Cat. 1 & 2
HP Required	16	35+
Belts	1 BX	3BX
Rotor Size	65 lbs.	165lbs.
Knives	(2) 2 1/2" x 3 1/2" x 5/16"	(4) 2 1/2" x 3 1/2" x 5/16"
Knife Bolts	3/8" Recessed & Hardened Bolts	3/8" Recessed & Hardened Bolts
Shear Bar/Anvil	Adjustable Hardened Anvil	Adjustable Hardened Anvil
Feed System	Manual Feed	Manual Feed
Hyd. Requirements	N/A	N/A
Self Contained Hyd. System	N/A	N/A
Feed Roller	N/A	N/A
Hopper Opening	25" x 18"	28" x 28"
Feed Height	38"	41"
Chip Chute	Fixed in 2 Positions	360° Rotation
Finish	Industrial Two-Part Urethane - Yellow	Industrial Two-Part Urethane - Yellow
Weight (lbs.)	375	650

Specifications subject to change without notice.

Distributed by ~



J.S. Woodhouse Co., Inc.

P.O. Box 1169, West Springfield, MA 01090

Tel. 413.736.5462 • Fax 413.732.3786

email: info@jswoodhouse.com • www.jswoodhouse.com