



AGRICULTURAL MACHINERY

sitrex®



FINISHING MOWERS

Distributed by: J. S. Woodhouse Co., Inc.
1314 Union St
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com

SM 230 P REAR DISCHARGE



Sitrex mower with five blades for a smooth cut and low horsepower requirement.

Suitable for parks, golf courses, athletic fields, highway maintenance and farming.

Solid rubber wheel (pneumatic wheel available on request).

- 1-1/4" diameter wheel post on pneumatic wheel
- Fully floating hitch to obtain better cutting finish even on undulating ground.
- Safety chain
- Designed according to the most advanced technics, heavy duty gearbox and thick gauge deck.
- Efficient Sitrex gearbox.
- Precision ball bearings.
- Nylon idler pulleys with ball bearings.
- Easy access grease points
- Easy to adjust belts
- Excellent cutter heads overlap for 100% cutting.
- Cutter blades of special steel, high suction for grass lifting and clean finish.
- Cutting height adjusted by spacer bushings placed on wheel's post.
- Optional front roller.



SPECIFICATIONS

CUTTING WIDTH	90"
CUTTING HEIGHT	1" to 4"
NUMBER OF BLADES	5
HP REQUIRED	30 to 60
BLADE RPM	2630
STANDARD PTO rpm	540
3 POINT HITCH	CATEGORY 1
WEIGHT LBS	683
STANDARD WHEELS	210X80

Distributed by: J. S. Woodhouse Co., Inc.
1314 Union St
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com

FRONT FINISHING MOWERS

SM 120F
SM 150F
SM 180F
SM 230F



Front finish mower available with gearboxes at 540-1000-2000 R.P.M. Clockwise or anti-clockwise direction of rotation. Two versions: rear and side discharge.

Through their adjustable hitches, front mowers can be fitted to any tractor provided with front hydraulic lift.

SPECIFICATIONS	SM 120 F	SM 150 F	SM 180 F	SM 230 F
CUTTING WIDTH	48"	60"	72"	90"
CUTTING HEIGHT	1" to 4"	1" to 4"	1" to 4"	1" to 4"
NUMBER OF BLADES	3	3	3	5
HP REQUIRED	12 to 20	15 to 30	20 to 40	30 to 60
BLADE RPM	3250	2630	2230	2630
PTO rpm	540/1000/2000 RH-LH			
3 POINT HITCH	CATEGORY 	CATEGORY 	CATEGORY 	CATEGORY
WEIGHT LBS	376	443	503	695
STANDARD WHEELS	210X80	210X80	210X80	210X80

SITREX s.p.A. reserves the right to make changes or add improvements at any time without notice. The information contained herein is general in nature and is not intended for specific application purposes.

Distributed by: J. S. Woodhouse Co., Inc.
1314 Union St
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com