

Hydraulic/PTO Concrete Mixers



Worksaver's Skid Steer Mixer, model SS-590 has direct hydraulic drive of the gearbox which eliminates chain and sprocket maintenance resulting in more up-time on the jobsite. Large 11-cubic ft. drum allows the operator to mix, transport and place 5-cubic ft. of concrete. It's efficient design offers the contractor a cost savings over chain driven models.

- All welded steel drum construction with internal paddles for uniform mixing and clean dumping.
- Compact, trouble free, long life design with few moving parts.
- Direct hydraulic drive of the gearbox eliminates chain & sprocket maintenance.
- Flow control valve allows easy control of mixer speed.
- All welded frame with store onboard parking stands for easy storage of the mixer when not in use.



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.

Concrete Mixer Specifications

SS-590	
Capacity	Five (5) cu/ft (1 Bag Mix)
Drum Opening (in/cm)	20 / 51
Overall Drum Length (in/cm)	32 / 81
Drum Construction	Welded Steel
Drive System	Hydraulic Direct Thru Gearbox
Hydraulic Requirements	Minimum 8 GPM
Hitch Requirements	N/A
Drive Ratio	3.18:1
Flow Control Valve	Standard
Connect Under Pressure Couplers	Standard
Parking Stands	Standard
Shipping Weight (lbs/kg)	395 / 180
Product No.	780950



Caution — A heavy load can cause your power unit to tip over. When moving heavy loads, keep the load as close to the ground as possible, go slowly around turns, and be sure the front or rear of tractor is properly counterbalanced with weights.

Caution — Operators must read & understand operator's manual, particularly the safety warnings and instructions. **The operator is responsible for safety of themselves and others when operating equipment.**



WORKSAVER, INC. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice.

WORKSAVER, INC. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.



Distributed by:

Worksaver, Inc.

P.O. Box 100, Litchfield, IL 62056-0100

Phone: 217-324-5973 • Fax: 217-324-3356

www.worksaver.com • E-mail: sales@worksaver.com



Designed. Engineered. Remarkable Value.