



## Pallet Forks

Designed for skid steer or tractor front loaders, our standard pallet forks have rated capacities from 4,000 lbs. to 5,500 lbs. All models feature solid steel alloy forks for long life, with spring loaded latches for easy adjustment spacing.

- Skid steer pallet forks (4,000 lbs.) are offered with a one piece backstop or a step through design for easy cab access and excellent visibility.
- Skid steer models mount with the "Universal" quick-attach mounting system.
- Premium forks include spring loaded latches for easy adjustment spacing.
- Models available with integrated brackets for skid steers, John Deere 400/500/600/700 series loaders, and loaders with euro/global attaching method.
- Pallet Forks for John Deere H480 loader with Global Series II tool carrier.
- Optional interfacing quick-attach brackets available for most other loader models.



## Pallet Fork Specifications

	For Skid Steer & Tractor Front Loaders the "Universal" Quick Attach System			For Tractor Loaders
Model	SSPF-442	SSPF-448S	SSPF-3748	PF-448
Equipment Used On	Skid Steer Loader	Skid Steer Loader	Skid Steer Loader	Tractor Loader
Capacity (lbs/kg)	4,000 / 1,814	4,000 / 1,814	4,000 / 1,814	4,000 / 1,814
Frame Construction	Welded Steel	Welded Steel	Welded Steel	Welded Steel
Backstop	Step-through	Step-through	Single Piece	N/A
Mounting	"Universal" Skid Steer	"Universal" Skid Steer	"Universal" Skid Steer	Mgt. Brt. Available*
Fork Spacing (in/mm)	6 - 40 / 152 - 1016	6 - 40 / 152 - 1016	6 - 40 / 152 - 1016	6 - 40 / 152 - 1016
Fork Carrier	Notched Rail	Notched Rail	Notched Rail	Notched Rail
Forks	1.375" x 4" w/Latch	1.375" x 4" w/Latch	1.375" x 4" w/Latch	1.375" x 4" w/Latch
Fork Length (in/mm)	42 / 1067	48 / 1219	48 / 1219	48 / 1219
Weight (lbs/kg)	345 / 157	359 / 163	315/143	438 / 199
Product No.	832400	832415	831370	831830

### John Deere Integrated Frame Pallet Forks

Model	JDPF-5442	JDPF-5448	JDPF-6748	JDPF-H48048	JDPF-H48060
Equipment Used On	JD Front Loader	JD Front Loader	JD Front Loader	JD Front Loader	JD Front Loader
Capacity (lbs/kg)	4,000 / 1,814	4,000 / 1,814	5,500 / 2,495	7,500 / 3,402	7,500 / 3,402
Frame Construction	Welded Steel	Welded Steel	Welded Steel	Welded Steel	Welded Steel
Mounting	400 / 500 Series JD	400 / 500 Series JD	600 / 700 Series JD	Global Series II	Global Series II
Fork Spacing (in/mm)	6-40 / 152-1016	6-40 / 152-1016	6-40 / 152-1016	6-40 / 152-1016	6-40 / 152-1016
Fork Carrier	Notched Rail	Notched Rail	Notched Rail	Notched Rail	Notched Rail
Forks	1.375" x 4" w/Latch	1.375" x 4" w/Latch	1.57" x 4" w/Latch	1.75" x 4.75"	1.75" x 4.75"
Fork Length (in/mm)	42 / 1067	48 / 1219	48 / 1219	48 / 1219	48 / 1219
Weight (lbs/kg)	345 / 157	359 / 163	373 / 169	785 / 356	845 / 383
Product No.	832420	832435	832440	834130	834140

### Global (Euro Hook Style) Integrated Frame Pallet Forks

Model	GLPF-442	GLPF-448	GLPF-5548
Equipment Used On	Tractor Front Loader	Tractor Front Loader	Tractor Front Loader
Capacity (lbs/kg)	4,000 / 1,814	4,000 / 1,814	5,500 / 2,495
Frame Construction	Welded Steel	Welded Steel	Welded Steel
Mounting	Euro / Global Carrier	Euro / Global Carrier	Euro / Global Carrier
Fork Spacing	6" to 40"	6" to 40"	6" to 40"
Fork Carrier	Notched Rail	Notched Rail	Notched Rail
Forks	1.375" x 4" w/Latch	1.375" x 4" w/Latch	1.57" x 4" w/Latch
Fork Length (in/mm)	42 / 1067	48 / 1219	48 / 1219
Weight (lbs/kg)	345 / 157	359 / 163	373 / 169
Product No.	832452	832458	832460

\*Optional interfacing quick attach brackets available for most popular loaders.

Note: Rated lift capacity is based on a pair of forks with no more than 1/2 - load per fork and load no more than halfway out on each fork.



**WARNING:** Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.