



Snow Blades

Designed for skid steers and tractor front loaders, heavy duty snow blades remove snow easily from driveways, parking lots or other large areas. Available in 5, 6, 7½ and 9 foot widths. 7½' and 9' blades feature 5 degree lateral oscillation allowing these wider blades to easily follow the ground contour. SBS models utilize the "Universal" skid steer mounting system. SBFL models offer interfacing brackets for most tractor front loaders. SBC models easily install on compact tractors by clamping onto the bucket for fast snow removal.

- Ideal for residential or commercial snow removal.
- Two trip springs for controlled break over in snow.
- Blade floats to clean uneven surfaces.
- Reinforced 21" or 27" high 10-gauge moldboards provide long service life.
- 3/8" x 6" reversible cutting edge of 1044 steel.
- Two clamp-on models for compact tractors.
- Step-through design allows for easy access to skid steer seat.
- Quick hook up on skid steers or front loaders equipped with "Universal" mounting plate.
- Select models integrate either the Euro/Global or John Deere 400/500 series mounting for easier hook up.
- Blade angles right or left.
- Adjustable skid shoes are ½" thick and rotate for longer life.



Adjustable skid shoes are standard



Snow Blades Specifications

For skid steers and tractors with a recommended HP of 40-95 HP.

	SBFL-27108A	SSB-27108A	SBG-27108A	SBJD-27108A	SBFL-2790A	SBS-2790A	SBG-2790A	SBJD-2790A
Overall Width (in/cm)	108 / 274	108 / 274	108 / 274	108 / 274	90 / 229	90 / 229	90 / 229	90 / 229
Overall Height (in/cm)	27 / 69	27 / 69	27 / 69	27 / 69	27 / 69	27 / 69	27 / 69	27 / 69
Moldboard Thickness	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge
Cutting Edge (in/mm) 3/8 x 6 / 9.525 x 152.4	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
5° Lateral Oscillation	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Extension Trip Springs	2	2	2	2	2	2	2	2
Manual Angle Positions	N/A	N/A	N/A	N/A	5	5	5	5
Width @ Full Angle	96 / 244	96 / 244	96 / 244	96 / 244	80 / 203	80 / 203	80 / 203	80 / 203
Tractor Loader Mount	*Brackets Req.	N/A	Euro / Global	400 / 500 JD	*Brackets Req.	N/A	Euro / Global	400 / 500 JD
Skid Steer Mount	N/A	Universal	N/A	N/A	N/A	Universal	N/A	N/A
Adjustable Skid Shoes	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Horse Power Rating	50-95 HP	50-95 HP	50-95 HP	50-95 HP	40-80 HP	40-80 HP	40-80 HP	40-80 HP
Weight (lbs/kg)	748 / 339	735 / 333	717 / 325	765 / 347	660 / 299	646 / 293	630 / 286	675 / 306
Hydraulic Angle Kit	Standard	Standard	Standard	Standard	Optional	Optional	Optional	Optional
Crossover Ref. Valve	Standard	Standard	Standard	Standard	Optional	Optional	Optional	Optional
Optional Top Deflector	360230	360230	360230	360230	360227	360227	360227	360227
Optional Sight Indicator	360235	360235	360235	360235	360235	360235	360235	360235
Product No.	360075	360070	360078	360275	360040	360000	360090	360270

*Optional interfacing quick attach brackets available for most popular models.



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.



Snow Blades Specifications

Models 2160 & 2172 are for skid steers and tractors with a recommended HP of 25-45 HP. SBC clamp-on models are for tractors with a recommended HP up to 35 HP.

	SBFL-2172	SBS-2172	SBC-2172	SBJD-2172	SBFL-2160	SBS-2160	SBC-2160	SBJD-2160
Overall Width (in/cm)	72 / 183	72 / 183	72 / 183	72 / 183	60 / 152	60 / 152	60 / 152	60 / 152
Overall Height (in/cm)	21 / 53	21 / 53	21 / 53	21 / 53	21 / 53	21 / 53	21 / 53	21 / 53
Moldboard Thickness	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge
Cutting Edge (in/mm) 3/8 x 6 / 9.525 x 152.4	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Extension Trip Springs	2	2	2	2	2	2	2	2
Manual Angle Positions	5	5	5	5	5	5	5	5
Width @ Full Angle	62 / 157	62 / 157	62 / 157	62 / 157	52 / 132	52 / 132	52 / 132	52 / 132
Tractor Loader Mount	*Brackets Req.	N/A	Clamp-On	200 / 400 JD	*Brackets Req.	N/A	Clamp-On	200 / 400 JD
Skid Steer Mount	N/A	Universal	N/A	N/A	N/A	Universal	N/A	N/A
Adjustable Skid Shoes	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Horse Power Rating	<45 HP	<45 HP	<35 HP	<45 HP	<45 HP	<45 HP	<35 HP	<45 HP
Weight (lbs/kg)	360 / 163	353 / 160	335 / 152	373 / 169	335 / 152	325 / 147	305 / 138	345 / 156
Hydraulic Angle Kit	Optional	Optional	N/A	Optional	Optional	Optional	N/A	Optional
Crossover Ref. Valve	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Optional Top Deflector	360223	360223	360223	360223	360220	360220	360220	360223
Optional Sight Indicator	360235	360235	360235	360235	360235	360235	360235	360235
Product No.	360160	360130	360290	360225	360140	360100	360280	360250

*Optional interfacing quick attach brackets available for most popular models.



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.