



*Designed. Engineered. Remarkable Value.*

## 20-Series Snow Pushers Designed for Sub-Compact Tractors



### **Worksaver's 20-Series Snow Pusher makes snow removal easy.**

Performance matched to fit Sub-Compact tractors up to 30 HP, the 20-Series snow pushers are sized to the tractor for maximum snow removal. Available in widths of 4' or 5', these pushers are offered with either a ultra rubber cutting edge or alloy steel cutting edge.

CNC formed 11-gauge mold-board with formed 10-gauge back brace for strength and durability make these snow pushers high performers.

Models are available with "universal" skid steer style mount or John Deere hook and pin style quick attach.



**worksaver.com**

*Engineered, Designed and Manufactured in the USA*

## 20-Series Snow Pusher Specifications

20-Series for Sub-Compact tractors up to 30 HP, Max. operating weight 1,800 lbs.  
"Universal" Skid Steer Attach



End plates with gentle slope design



Adjustable Skid Shoes of AR-400 material

	SPS-2048R	SPS-2048M	SPS-2060R	SPS-2060M
Overall Width (in/mm)	52 / 1321	52 / 1321	64 / 1626	64 / 1626
Overall Height (in/mm)	21.5 / 546	21.5 / 546	21.5 / 546	21.5 / 546
Overall Depth (in/mm)	21 / 533	21 / 533	21 / 533	21 / 533
Moldboard Thickness	11-gauge	11-gauge	11-gauge	11-gauge
End Plate Thickness	7-gauge	7-gauge	7-gauge	7-gauge
Inside Angle Bracing	Yes	Yes	Yes	Yes
Rubber Cutting Edge	Yes (1" x 4")	No	Yes (1" x 4")	No
Alloy Steel Cutting Edge	No	Yes (3/8" x 4")	No	Yes (3/8" x 4")
Skid Shoes of AR-400	Yes	Yes	Yes	Yes
Horsepower rating	Up to 30 HP	Up to 30 HP	Up to 30 HP	Up to 30 HP
Weight (lbs./kg)	146 / 66	163 / 74	159 / 72	180 / 82
Product No.	358160	358165	358170	358175
Optional Pull-back Kit	358200	358200	358205	358205

20-Series for Sub-Compact tractors up to 30 HP, Max. operating weight 1,800 lbs.  
John Deere hook & pin quick attach for 200/300, D120, H120, H130

	SPJD-2048R	SPJD-2048M	SPJD-2060R	SPJD-2060M
Overall Width (in/mm)	52 / 1321	52 / 1321	64 / 1626	64 / 1626
Overall Height (in/mm)	21.5 / 546	21.5 / 546	21.5 / 546	21.5 / 546
Overall Depth (in/mm)	21 / 533	21 / 533	21 / 533	21 / 533
Moldboard Thickness	11-gauge	11-gauge	11-gauge	11-gauge
End Plate Thickness	7-gauge	7-gauge	7-gauge	7-gauge
Inside Angle Bracing	Yes	Yes	Yes	Yes
Rubber Cutting Edge	Yes (1" x 4")	No	Yes (1" x 4")	No
Alloy Steel Cutting Edge	No	Yes (3/8" x 4")	No	Yes (3/8" x 4")
Skid Shoes of AR-400	Yes	Yes	Yes	Yes
Horsepower rating	Up to 30 HP	Up to 30 HP	Up to 30 HP	Up to 30 HP
Weight (lbs./kg)	131 / 59	148 / 67	145 / 66	166 / 75
Product No.	358180	358185	358190	358195
Optional Pull-back Kit	358200	358200	358205	358205



**Caution** — A heavy load can cause your power unit to tip over. When moving heavy loads, keep the load as close to the ground as possible, go slowly around turns, and be sure the front or rear of power unit is properly counterbalanced with weights.

**Caution** — Operators must read & understand operator's manual, particularly the safety warnings and instructions. **The operator is responsible for safety of themselves and others when operating equipment.**



WORKSAVER, INC. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. WORKSAVER, INC. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.



Distributed by:



**Worksaver, Inc.**

P.O. Box 100, Litchfield, IL 62056-0100

Phone: 217-324-5973 • Fax: 217-324-3356

worksaver.com • E-mail: sales@worksaver.com

**Designed. Engineered. Remarkable Value.**





## Snow Pushers - 24 Series

Engineered to fit Compact and Sub-Compact tractor. The 24-Series Snow Pusher is job matched to the tractor for maximum performance.

- Replaceable 1" x 6" reversible rubber cutting edge is standard on "R" models
- Replaceable 3/8" x 6" reversible steel cutting edge is standard on "M" models
- Models to fit loaders with "Universal" skid steer attaching system.
- Models to fit John Deere 200/300/400 series loaders with quick attach system.
- All models feature adjustable & reversible skid shoes of high abrasive resistance steel.



### Snow Pushers Specifications

24-Series for Tractors up to 50 HP, Max. Operating Weight 3,500 lbs. - "Universal" Skid Steer Attach

	SPS-2460R	SPS-2460M	SPS-2472R	SPS-2472M	SPS-2484R	SPS-2484M
Overall Width (in/cm)	66.5 / 169	66.5 / 169	78.5 / 199.4	78.5 / 199.4	90.5 / 230	90.5 / 230
Overall Height (in/cm)	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65
Overall Depth (in/cm)	26 / 66	26 / 66	26 / 66	26 / 66	26 / 66	26 / 66
Moldboard Thickness	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge
End Plate Thickness (in/cm)	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635
Reinforced Endplates	Yes	Yes	Yes	Yes	Yes	Yes
Rubber Cutting Edge	Yes	No	Yes	No	Yes	No
Steel Cutting Edge	No	Yes	No	Yes	No	Yes
Adjustable/Reversible Skid Shoes	Std.	Std.	Std.	Std.	Std.	Std.
Horsepower Rating	20-30 hp.	20-30 hp.	25-40 hp.	25-40 hp.	30-50 hp.	30-50 hp.
Weight (lbs/kg)	390 / 177	410 / 186	430 / 195	450 / 204	465 / 211	485 / 220
Product No.	358000	358005	358010	358015	358020	358025

### Snow Pushers Specifications

24-Series for Tractors using John Deere 200/300/400 attaching system on tractors up to 50 HP, Max. Operating weight 3,500 lbs.

	SPJD-2460R	SPJD-2460M	SPJD-2472R	SPJD-2472M	SPJD-2484R	SPJD-2484M
Overall Width (in/cm)	66.5 / 169	66.5 / 169	78.5 / 199.4	78.5 / 199.4	90.5 / 230	90.5 / 230
Overall Height (in/cm)	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65
Overall Depth (in/cm)	26 / 66	26 / 66	26 / 66	26 / 66	26 / 66	26 / 66
Moldboard Thickness	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge
End Plate Thickness (in/cm)	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635
Reinforced Endplates	Yes	Yes	Yes	Yes	Yes	Yes
Rubber Cutting Edge	Yes	No	Yes	No	Yes	No
Steel Cutting Edge	No	Yes	No	Yes	No	Yes
Adjustable/Reversible Skid Shoes	Std.	Std.	Std.	Std.	Std.	Std.
Horsepower Rating	20-30 hp.	20-30 hp.	25-40 hp.	25-40 hp.	30-50 hp.	30-50 hp.
Weight (lbs/kg)	379 / 172	399 / 181	415 / 188	435 / 197	450 / 204	470 / 213
Product No.	358030	358035	358040	358045	358050	358055



**WARNING:** Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.



## Mini Skid Steer Snow Blades

Designed for Mini Skid Steers / Compact Tool Carriers, this 50" snow blade is ideal for clearing sidewalks, eliminating hand shoveling. Incorporating many of the features of our larger snow blades, this blade consistently delivers the performance you demand.

- Two trip springs for controlled breakover in snow
- 3/8" x 6" reversible cutting edge
- Standard Skid Shoes of abrasive resistance steel

### Mini Skid Steer Snow Blade Specifications

	SBMS-50	SBMS-50 B/G
Overall Width (in/cm)	50 / 127	50 / 1270
Overall Height (in/cm)	21 / 53.34	21 / 53.34
Moldboard Thickness	10-gauge	10-gauge
Cutting Edge (in/cm)	3/8 x 6 / 0.9525 x 15.24	3/8 x 6 / 0.9525 x 15.24
Mount	Universal Mini Skid	Bobcat MT / Gehl*
Weight (lbs/kg)	280 / 127	280 / 127
Product No.	360245	360260

\* Note: Also for Bobcat S-70 & Gehl 1640 small cab type units.

## Snow Pushers - 36 Series

Engineered for Skid Steer loaders and Utility tractors from 50-90 hp. (depending on model) these 36-series Snow Pushers consistently deliver the high performance today's large property owners demand. They feature an adjustable & reversible 1.5" x 8" premium rubber cutting edge, 4-inch wide reversible skid shoes of abrasive resistant steel and 7-gauge moldboard. Models are available to fit "universal" skid steer attaching system, John Deere 400/500 attaching system and the Global / Euro tool carrier.

### Snow Pushers Specifications

36-Series for Skid Steers and Utility Tractors from 50-90 HP (depending on model)

	SPS-3696R	SPJD-3696R	SPG-3696R	SPS-36120R	SPJD-36120R	SPG-36120R
Overall Width (in/cm)	104.5 / 265	104.5 / 265	104.5 / 265	128.5 / 326	128.5 / 326	128.5 / 326
Overall Height (in/cm)	37.37 / 95	37.37 / 95	37.37 / 95	37.37 / 95	37.37 / 95	37.37 / 95
Overall Depth (in/cm)	37.75 / 96	37.75 / 96	37.75 / 96	37.75 / 96	37.75 / 96	37.75 / 96
Moldboard Thickness	7-gauge	7-gauge	7-gauge	7-gauge	7-gauge	7-gauge
Endplate Thickness (in/cm)	5/16 / 0.795	5/16 / 0.795	5/16 / 0.795	5/16 / 0.795	5/16 / 0.795	5/16 / 0.795
Reinforced Endplates	Yes	Yes	Yes	Yes	Yes	Yes
Rubber Cutting Edge	Yes	Yes	Yes	Yes	Yes	Yes
Adjustable/Reversible Skid Shoes	Std.	Std.	Std.	Std.	Std.	Std.
Horsepower Rating	50-80 hp.	50-80 hp.	50-80 hp.	50-90 hp.	50-90 hp.	50-90 hp.
Mounting	Skid Steer	JD 400/500	Euro/Global	Skid Steer	JD 400/500	Euro/Global
Product No.	358060	358070	358080	358090	358100	358110