



		CONSTRUCTION					
		20		24		34	
		in	mm	in	mm	in	mm
A	Overall Height	116	2,946	119	3,023	133	3,378
B	Body Length	192	4,877	216	5,486	263	6,680
C	Overall Length	258	6,553	283	7,188	341	8,661
D	Floor to top of Side	30	762	33	838	37	940
E	Width of Floor Front	80	2,032	87	2,210	88	2,235
F	Width of Floor Back	82	2,083	89	2,261	91	2,311
G	Inside Body Width at Front	89	2,261	96	2,438	97	2,464
H	Inside Body Width at Back	93	2,362	99	2,515	101	2,565
I	Overall Width	110	2,794	120	3,048	122	3,099
J	Tipping Angle	58		57		59	
K	Max Height when Tipped	232	5,893	252	6,401	295	7,493
L	Max Height when Tipped (Extension)	242	6,147	263	6,680	306	7,772
M	Ground to Box Floor (Standard tires)	59	1,499	59	1,499	67	1,702
N	Turning Clearance	83	2,108	83	2,108	92	2,337
O	Ground Clearance	21	533	21	533	24	610
P	Ground to Box Side	89	2,261	92	2,337	104	2,642
Q	Ground to Box Extension (Inc 6" Standard)	95	2,413	98	2,489	110	2,794
R	Ground to Box Extension (Inc 20-24 = 12") (34 = 14")	101	2,565	104	2,642	116	2,946
S	Ground to Box Extension (Inc 24" Extensions)	113	2,870	116	2,946	128	3,251
	Floor Thickness	0.188	5	0.25	6	0.25	6
	Volume (Struck) Box with standard 6" extension	13	9.9	17.8	13.6	25	19.1
	Volume (Heaped) Box Only	14.4	11.0	19.6	15.0	27.5	21.0
	Volume (Heaped) (20-24, 12 inch) (34, 14 inch)	20.2	15.4	23.3	17.8	32	24.5
	Volume (Heaped) (24" Light Material)	25.9	19.8	32.7	25.0	43.8	33.5
	Drawbar Suspension	Rubber		Rubber		Rubber	
	Wheel Hub	10 Bolt 11.250 centers		10 Bolt 11.250 centers		10 Bolt 13.188 centers	
	Brake Axles (Recommended)	X 0		X 1		X 2	
	Tires (Recommended)	710-50/26.5		750-45/26.5		750-60/26.5	
	Tongue Weight Empty	1,400	635	2,100	952	2,300	1,043
	Tongue Weight Loaded	5,500	2,494	8,100	3,673	9,000	4,082
	Empty Weight (Approx.)	15,000	6,803	20,000	9,070	27,000	12,245

2021-10



Construction Trailers



▶ North American made,
▶ with a European touch on design and finish.



"PATENTED" HIGH CLEARANCE TAILGATE

24" Silage sides can be added with the High clearance tailgate design.



"Patented" High clearance tailgate, gets the door out of the way for when loading brush, trees and anything long or bulky.

SINGLE MULTISTAGE CYLINDER

" Patent pending" Hyd slave system: This boosts the amount of oil your tractor provides and eliminates the need for on-board pumps and tanks etc on the trailer.



Single, Multi-stage dump cylinder: Requires less oil from the tractor, accommodating older, smaller tractors with limited oil capacity.

NORTH AMERICAN AXLES / HIGHWAY TRUCK BRAKES



North American axles / Highway truck brakes: Makes spare wheels and axle/brake parts easier to find. Removable stub axles for any major repairs.

HARDOX BODY



Tapered body, helps to reduce the drag on the walls when dumping, the load ejects easier and at a lower height than straight walls.

ADJUSTABLE RUBBER RIDE HITCH



Adjustable rubber ride hitch: Reduces jumping on the hitch through rough ground or at speed.

ROAD LIGHT KIT, FENDERS & MUDFLAPS



SWIVEL BALL HITCH



HYDRAULIC JACK

