



50 YEARS
OF EXPERTISE
TO SHARE

LEAF & DEBRIS BLOWER

FOR THREE POINT HITCH

DB6000



HIGH VELOCITY

INNOVATION, OUR PASSION

www.radinter.com

SPECIFICATIONS

MODEL	DB6000
Power source	30HP tractor - PTO 540 rpm 25 HP PTO
Category Compatibility 3 point	Standard cat. 1 & cat. 2
Quick Hitch Compatibility	ASABE Compatible Cat. 1 & 2
Air flow	6061 cfm
Impeller dimension	29 3/4" x 10" - 12 blades
Impeller speed	1453 rpm to 540 rpm
Air velocity	141 m/h - 227 km/h
Outlet area	70.4 cu.in - 454.2 cu.cm
Drive	Belt 4-5VX560 "power band"
Driveline	40 series
Directional control	Manual Panel - left or right
Ground clearance	3 1/8"
Height adjustment	Determined by tractor
Caster wheel	3 wheels - 12" dia. x 3" pneumatic
Impeller housing	Rear & front panel: 10ga Housing edge: 12ga
Dimension	54 1/2" length x 48 1/2" height x 49 1/4" width
Weight	655 lbs

Distributor

Manufactured by:



Intertek

RADTECH INNOVATION

Division of RAD TECHNOLOGIES INC.

2835, Chemin de l'Aéroport

Thetford Mines (Quebec) Canada G6G 5R7

☎ 418 338-4499 | 1 800 338-1615

📠 418 338-6090 ✉ radtech@radinter.com