

LIBRA SINGLE BEAM PLOWS

FEATURES:

- Plows include 1 gauge wheel & 1 disc opener per bottom
- Overload protection by springs
- Hydraulic adjustment of working width is 12"- 20"
- Working depth: Up to 14"
- Distance between plow bodies: 35"
- Height under frame: 33"



LIBRA SINGLE BEAM PLOWS

MODELS	HITCH CATEGORY	DESCRIPTION	HORSEPOWER REQUIRED	WEIGHT
U068	II	3-Bottom, Full Frame	74-90	2024
U068/1	II	4-Bottom with Extensions 3+1=4	100-120	2464
U068/2	II	4-Bottom, Full Frame	100-120	2464
U068/3	II	5-Bottom with Extension 4+1=5	125-150	2926

POTATO PLANTERS

GEMINI ONE-ROW POTATO PLANTER

FEATURES:

- During a single cycle, all of the potato planting functions are performed (furrowing, seeding, and ridging the seeded plants with soil).
- Potatoes can be planted at 3 variable distances in a row within the metal wheels and a constant distance with the rubber wheels. Changing the diameter of the wheels changes the seed distance.



GEMINI ONE ROW POTATO PLANTER

MODELS	DESCRIPTION	HITCH CATEGORY	SEED DISTANCE	PLANTING DEPTH	HORSEPOWER REQUIRED	HOPPER CAPACITY	WEIGHT
S239/2-S	With Steel Wheels	I	11.5", 12.5", 13"	4"-6"	20	198 lbs.	286
S239/2-R	With Rubber Tires	I	12.5"	4"-6"	20	198 lbs.	286
Optional Rubber Tank Cover for Hopper Bottom							
Optional Set of Buckets for Planting Small-Size Potatoes							

POTATO DIGGERS

URSA ONE ROW POTATO DIGGER

FEATURES:

- Rear discharge ploughshare w/ adjustable digging depth transfers potatoes & soil onto the vibrating hopper, sifting potatoes from soil.
- Digging depth adjusted by rear support wheels.
- All vibrating elements moved by crank mechanism driven from the tractor PTO shaft.



URSA ONE ROW POTATO DIGGER

MODELS	HITCH CATEGORY	SHARE WIDTH	HORSEPOWER REQUIRED	MAXIMUM WORKING DEPTH	WEIGHT
Z655/1	I	18"	10	8"	297