

POWER HARROW



SHAKTIMAN Power Harrow is suitable for the crops which require deeper tillage like Potato and tuber crops. Its boron steel long blades help achieve deep tillage in any type of soil. It reduces the number of tillage operations reducing number of passes, thus help in reducing compaction of soil. It comes

with option of multispeed to adjust speed as per the customer's requirements. The leveling bar is a standard feature and accessories consist of three types of Rollers: Packer Roller, Spike roller & Cage Roller



World's Largest Manufacturer of Rotary Tiller

POWER HARROW

Model	Speed	L x W x H (mm)	Working Width (mm/inch)	 HP Kw	 No. of Blades	 Weight(Kg/lbs)
SRP-75	Single	1500 x 869 x 1210	750 / 29.5	35-50 26-37	6	400 / 880
SRP-100	Single/Multi	1500 x 1120 x 1210	1000 / 39.4	45-60 34-45	8	460 / 1012
SRP-125	Multi	1500 x 1365 x 1210	1250 / 49.2	55-70 41-52	10	500 / 1100
SRP-150	Multi	1500 x 1610 x 1210	1500 / 59.1	60-75 45-56	12	545 / 1199
SRP-175	Multi	1500 x 1855 x 1210	1750 / 68.9	65-80 48-60	14	590 / 1298
SRP-200	Multi	1500 x 2100 x 1210	2000 / 78.7	70-85 52-63	16	640 / 1408
SRP-225	Multi	1500 x 2345 x 1210	2250 / 88.6	75-90 56-67	18	680 / 1496
SRP-250	Multi	1500 x 2590 x 1210	2500 / 98.4	80-95 60-71	20	720 / 1584
SRP-275	Multi	1500 x 2835 x 1210	2750 / 108.3	85-100 63-75	22	760 / 1672
SRP-300	Multi	1500 x 3080 x 1210	3000 / 118.1	90-105 67-78	24	800 / 1760
SRP-350	Multi	1500 x 3570 x 1210	3500 / 137.7	100-115 75-86	28	880 / 1940

Roller	Roller Dia (mm / inch)	Teeth Length (mm / inch)
PACKER 420	420 / 16.5	64.5 / 2.5
PACKER 450	450 / 17.7	78 / 3
SPIKE	504 / 19.9	197 / 7.8
CAGE	383 / 15.1	NA

Standard Gear Pair 16-19

The company reserves absolute rights to modify the specifications of machine and components the rein without any prior notice.

"Weight is including safety guards & excluding PTO & Roller Assembly"

*Accessories shown are not part of standard equipment.

Advantages

- Its long and sharp blades can easily plough any land and achieve tillage depth up to 10 inches.
- Its sturdy structure is welded with high thickness plates which make sure that it operates under toughest conditions.
- Its Gear Box designed with quality components enhances durability of the implement.
- It ensures faster operation and completes function in less time reducing fuel consumption and soil compaction.

Features



Swinging brackets




Blades with 12 mm/0.47 inch thickness and 285 mm/11.22 inch length made of boron steel material



Rear leveling bar with pin or screw adjustment



Multi speed gearbox for 540 & 1000 RPM PTO



Single speed gearbox for 540 RPM PTO

Universal joint power transmission shaft with clutch



Floating side plates

Accessories



Spike Roller



Packer Roller



Cage Roller

Scan to Visit Website



Tirth Agro Technology Pvt. Ltd.

"SHAKTIMAN", Survey No.-108/1, Plot No. B, NH-27, Nr. Bharudi Toll Plaza, Bhunava (Village), Taluka: Gondal, Dist.: Rajkot.
State: Gujarat - INDIA, Pin - 360 311. Phone: + 91 (2827) 661637 (30 Lines), + 91 (2827) 270 537, Fax: + 91 (2827) 270 457
Email: info@shaktimanagro.com, Web: www.shaktimanagro.com, CIN: U72900GJ2000PTC 038435

Correspondence : Nr. Hotel Krishna Park, N.H. 27, Vavdi, Rajkot - 360 004, Gujarat, India.

World's Largest Manufacturer of Rotary Tillage