



Sipma 3-Point Bale Wrapper



Shown with optional bale turner

FEATURES:

- Tilt Table: Allows discharge of wrapped bales. After unlocking the latch, the tilt table is lifted by the tractor's hydraulics system and the bale rolls off.
- Attach the film to the first bale and after discharging each bale the plastic is cut. The operator then will load the next bale on the wrapper table on top of the film, not requiring fixing the film to the bale.
- Solid frame: stable & resistant to overload
- 750 mm (30") film requires only 16 wrapping revolutions
- Aluminum milled film dispenser rollers
- Bale counter: indicates number of film layers and end wrapping process

SPECIFICATIONS - 7500 Sipma Wrapper	
Model No.	7500
Wrapping Time	1 Minute
Bales Diameter	1300mm/4 ft.
Bale Width	1250mm/4 ft
Maximum Bale Weight	1000kg/2200 lbs
Minimum # of Wrapping	2 times
Dimensions	103" L x 47" W x 47" H
Tractor Requirement	Cat 11/38 HP minimum
Hydraulic Requirements	1 Set of remotes - approx 6.6 GPM
Foil Width	500/700 mm - 20"/30"
Machine Weight	1056 lbs
1600-200 Bale Turner	88 lbs (optional)
Use	7500 designed for small/medium farms

Specifications subject to change without notice.

Distributed by ~



J.S. Woodhouse co., Inc.

P.O. Box 1169, West Springfield, MA 01090

Tel. 413.736.5462 • Fax 413.732.3786

email: info@jswoodhouse.com • www.jswoodhouse.com