

# TRYGG FAST TRAC



## Farm tractor

TRYGG Fast Trac



9 mm - 3/8"

7 mm - 9/32"

- High strength steel, deep case hardened
- Multi fit design
  - remove side links and crossers to shorten the chains for a perfectly snug fit
- Continuous traction and grip, twisted links keep studs up on top of the lugs
- Ground penetration, grip and service life equal to 3/8" chains that are 30% extra weight and cost
- Low profile needs only 2" side wall clearance and 3" fender clearance

### Fast Trac 8 mm - 5/16"

Item #	Item #	Item #	Item #	Item #	Item #
581010	581015	581020	581025	581030	581035
113 kg	96 kg	90 kg	82 kg	71 kg	68 kg
248 lbs	211 lbs	198 lbs	180 lbs	156 lbs	149 lbs
18,00-33	16,9-38	14,9-28	18,4-24	13,00-24	11,2-24
20,8-34	18,00-24/25	14,9-30	14,00-24/25	14,9-20	11,2-28
20,8-38	18,4-30	14,9-38	17,5-24	14,9-24	12,00-24
20,8-42	18,4-34	15,5-38	17,5-25	15-19,5	12,4-20
23,1-26	18,4-38	16,00-24/25	19,5L-24	*15,5-24	12,4-24
23,1-30	20,5-25	16,9-24	480/60-28	*15,5-25	12,4-28
23,1-34	420/85-38	16,9-26	480/65-24	340/85-28	*13,6-16
23,5-25	460/85-34	16,9-28	480/65-28	360/70-24	13,6-24
24,5-32	480/70-30	16,9-30	480/70-24	360/70-28	13,6-28
520/70-38	480/70-34	16,9-34	480/70-28	360/80-24	280/85-28
520/85-38	480/70-38	17,5-25 L5	495/70-25	365/80-20	300/70-24
520/85-42	480/80-30	18,4-26	500/60-26,5	365/85-20	320/70-24
540/80-38	480/80-34	20,5-25	500/65-26,5	375/75-20	320/70-28
580/70-34	480/80-38	380/85-28	500/65-28	380/70-20	320/85-24
580/70-38	520/70-30	380/85-30	520/60-28	380/70-24	320/85-28
580/70-42	520/70-34	385/95-25	520/65-24	380/70-28	325/95-24
600/55-38	540/65-30	400/80-28	520/65-28	380/85-24	340/80-24
600/60-28	540/65-34	420/70-30	525/65-20,5	395/80-20	340/85-24
600/60-30	540/65-38	420/70-34	540/65-24	400/65-24	360/70-20
600/60-38	540/70-30	420/85-28	540/65-28	400/80-24	
600/65-28	540/70-34	420/85-30		405/70-18	<b>Item #</b>
600/65-34		420/85-34		405/70-20	<b>581040</b>
600/65-38		440/80-24		405/70-24	<b>41 kg</b>
600/70-28		440/80-28		420/65-20	<b>90 lbs</b>
600/70-30		440/80-30		420/65-24	11,2-16
600/70-34		440/80-34		420/70-24	12,4-16
620/70-42		460/65-24		420/85-24	13,06-16
620/75-30		480/65-28		43-16-20	
650/60-34		480/70-28		440/65-24	
650/60-38				43-16-20	
650/65-34				15-19,5	
650/65-38				15,5-24	
650/65-42				14,9-26	
650/75-38				400/70-18	
				41x14-20	

Your size not shown? Call to find out your category!

# TRYGG ALL TERRAIN

## Compact Tractor & ATV



- Aggressive grip
- Light weight
- Two studs on every second link increases ground penetration
- Diamond Pattern stays on top of the lugs for continuous grip
- Low profile, needs 1 1/2 inch side wall clearance and 2" inch fender clearance
- Flexible diamond pattern ensures tight fit to new and worn down tires
- High strength steel, deep case hardened



TRYGG ATV

### All Terrain 6 mm / 1/4"

Item #	Item #	Item #	Item #	Item #	Item #
425220	425225	425250	425356	425358	425360
30 lbs	33 lbs	37 lbs	50 lbs	54 lbs	55 lbs
23x8.00-12	24x10.5-12	25x12.50-10	12-16.5	7.50-18	11.2-16
23x8.50-12	25x10.00-12	25x12.50-12	33x12.5-15	8.00-18	12.4-16
23x8.50-14	25x10.00-10	26x10.00-12	10-16.5	8.3-22	13.6-16
23x10.50-12	26x8.00-12	26x10.50-12	12.0/75-18	8.3-24	
23x10.00-10	24x8-12	26x11.00-12	13/70-16		
24x9.00-11	26x8.00-14	26x12.0-12	260/80-20		
24x8.50-14	24x8.50-12	27x9.00-12	33x12.5-16.5		
24x9.00-12	205/65-15	27x12.00-12	12.5-16.5		
25x8.00-12	205/85-12	27x9.00-14	29x12.50-15		
220/55-12	23x10.50-12	27x11.00-14			
	26x9.00-12	26x11.00x12			
	25x8.50x14	11.0/65-12			
		27x8.5-15			

Nøsted &  
 Grønviksveien 8  
 N-4515 Mandal, Norway  
 Tel: +47 38 27 25 50  
 Fax: +47 38 27 25 51  
 E-mail: [post@trygg.no](mailto:post@trygg.no)  
 Homepage: [www.trygg.no](http://www.trygg.no)

