



Designed. Engineered. Remarkable Value.

Land Management Equipment Solutions for Hard Work



www.worksaver.com

Engineered, Designed and Manufactured in the USA



The widest choice of quality land management attachments.



Rotary Brooms

Designed for use by contractors, municipalities, institutions and farmers. Hydraulically driven models for skid steers, PTO driven models for 3-pt. tractor mounts (Cat.I). 32 inch diameter convoluted brushes available in Poly (P) or both Poly and Wire (PW). All models available in 5-ft., 6-ft., & 7-ft. widths.

- Remove dirt, sand, gravel and trash from construction entrances, parking lots, bridges, driveways & sidewalks.
- Remove thatch and prepare turf for the growing season.
- Clean snow or leaves from streets, driveways, and building entrances.
- Excellent for general clean up before sealing or repairing pavement.
- Brooms angle up to 30-degrees right or left. Optional manual or hydraulic angle adjustment kits available.
- Height adjustment chains maintain an even operating position.
- Parking stand included as standard equipment.

Skid Steer Rotary Broom

- Hydraulically driven skid steer models in 5-ft., 6-ft., & 7-ft. widths with 32" diameter brushes.
- Variable flow control valve for optimum broom speed.
- Step-through mount design for easy in/out of skid steer cab.
- Optional electric solenoid kit also offered.
- 4.36/1 chain drive ratio provides job matched torque to get through tough conditions.

3-pt. Rotary Broom

- PTO driven 3-pt. tractor mount in 5-ft., 6-ft., & 7-ft. widths with 32" diameter brushes.
- Double gearbox drive with patented top "T-shaft" for smooth power transmission and easy reversal of brush rotation.
- Designed for Category I tractors with 1,000 lbs. or greater 3-pt. lift capacity.

Skid Steer Rotary Broom Specifications

	SSMB-325P	SSMB-325PW	SSMB-326P	SSMB-326PW	SSMB-327P	SSMB-327PW
Overall Width (in/cm)	69 / 175	69 / 175	81 / 206	81 / 206	93 / 236	93 / 236
Brush Diameter (in/cm)	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81
Sweeping Width (in/cm)	60 / 152	60 / 152	72 / 183	72 / 183	84 / 213	84 / 213
Width @ 30° Angle (in/cm)	53 / 135	53 / 135	64 / 163	64 / 163	76 / 193	76 / 193
Mounting System	Skid Steer					
Brush Material	Poly	Poly / Wire	Poly	Poly / Wire	Poly	Poly / Wire
Hydraulic Motor Rating	16 GPM					
Oil Flow Requirement (gpm/lpm)	12-30 / 45-114	12-30 / 45-114	12-30 / 45-114	12-30 / 45-114	12-30 / 45-114	12-30 / 45-114
Dirt Deflector	Optional	Optional	Optional	Optional	Optional	Optional
Weight (lbs/kg)	640 / 290	637 / 289	740 / 336	736 / 334	840 / 381	833 / 378
Product No.	610961	610960	610966	610965	610971	610970

 **WARNING:** Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.

3-pt. Rotary Broom Specifications

	RMB-325P	RMB-325PW	RMB-326P	RMB-326PW	RMB-327P	RMB-327PW
Overall Width (in/cm)	69 / 175	69 / 175	81 / 206	81 / 206	93 / 236	93 / 236
Brush Diameter (in/cm)	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81
Sweeping Width (in/cm)	60 / 152	60 / 152	72 / 183	72 / 183	84 / 213	84 / 213
Width @ 30° Angle (in/cm)	53 / 135	53 / 135	64 / 163	64 / 163	76 / 193	76 / 193
Mounting System	3-pt. (Cat. I)					
Brush Material	Poly	Poly / Wire	Poly	Poly / Wire	Poly	Poly / Wire
PTO RPM Range	540	540	540	540	540	540
Dirt Deflector	Optional	Optional	Optional	Optional	Optional	Optional
Weight (lbs/kg)	720 / 326	714 / 324	780 / 354	774 / 351	840 / 381	833 / 378
Product No.	610705	610700	610755	610750	610805	610800

 **WARNING:** Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.

Options

Angle Adjustments Kits (all models require either a manual or hydraulic kit)	
Product No. 610702	Manual Angle Adjustment Kit for either skid steers or 3-pt. tractor.
Product No. 610703	3-pt. Hydraulic Angle Adjustment Kit – includes cylinder & hoses less tips.
Product No. 610704	Skid Steer Hydraulic Angle Adjustment Kit – includes electric hydraulic solenoid control valve. For skid steer brooms used on units with only one set of remotes. Includes cylinder, hoses, valve, & flat-faced couplers. Factory installed.
Electric Solenoid Kit (Optional)	
Product No. 610950	Field installed electric hydraulic solenoid valve kit – fits product no. #610703 hydraulic angle kit above.



SmoothCut™ Stump Grinders

Economical and efficient PTO powered stump grinders make stump removal fast and easy. Operator easily controls the grinder from the comfort of the tractor seat. Surefoot™ stabilizer provides solid footing during operation.

- Tractor models require two pair of remote hydraulic outlets.
- Cutting wheel design provides a smoother cutting action and higher productivity.
- Durable carbide-tipped cutting teeth are economical and easy to replace.
- Maneuverable – goes anywhere a tractor can; gets into tight places.
- Easy to operate – hydraulic controls allow easy operation from the seat of the tractor using existing hydraulic controls.
- Heavy duty bushings w/grease zerks are used at major pivot points for increased reliability and extended service life.
- Standard pressure relief valve for precise control of cutting feed rate.
- Pressure relief valve helps reduce hydraulic oil heat buildup keeping tractor hydraulics cooler.
- Rubber deflector helps control chips and debris during grinding.
- Parking stand for easy storage.



Surefoot™ stabilizer

Stump Grinder Specifications

	SG-26A	SG-36A
Hitch	Cat. I	Cat. I / II
Overall Estimated Length (in/cm)	75 / 191	80 / 230
Drive System Protection	Slip Clutch	Slip Clutch
Gearbox Rating / Ratio	60 HP / 1:1.5	100 HP / 1:1.46
Cutting Wheel Construction	Welded 2-piece Laminated Steel	
Cutting Wheel Thickness (in/cm)	3/4 / 1.91	7/8 / 2.22
Cutting Wheel Diameter (in/cm)	26 / 66	36 / 91
Cutting Wheel Speed	810 RPM	788 RPM
@ 540 PTO RPM	5,515 ft. / min.	7,430 ft. / min.
Number of Teeth	33	42
Cutting Teeth Construction	Carbide Steel Bolt-in	
Cut Height Above Ground (in/cm)	18 / 46	18 / 46
Cut Depth Below Ground (in/cm)	10 / 25	15 / 38
Maximum Horizontal Cut (in/cm)	28 / 71	33 / 84
Swing Arc	45°	45°
Minimum Power / Flow Required	22-PTO HP	45-PTO HP
Maximum Power / Flow	50-PTO HP	100-PTO HP
Driveline	PTO / Series 5	PTO / Series 6
PTO Speed	540 RPM	540 RPM
Weight (lbs/kg)	660 / 299	880 / 399
Product No.	812200	812210



WARNING: Read and understand the operator's manual before operation. Stump grinder will put a heavy load on the rear of your tractor. Be sure your tractor is properly counterbalanced. Damage to equipment or personal injury could occur. Never allow children or bystanders around tractor or stump grinder while operating.



Snow Blades

Designed for skid steers and tractor front loaders, heavy duty snow blades remove snow easily from driveways, parking lots or other large areas. Available in 5, 6, 7½ and 9 foot widths. 7½' and 9' blades feature 5 degree lateral oscillation allowing these wider blades to easily follow the ground contour. SBS models utilize the "Universal" skid steer mounting system. SBFL models offer interfacing brackets for most tractor front loaders. SBC models easily install on compact tractors by clamping onto the bucket for fast snow removal.

- Ideal for residential or commercial snow removal.
- Two trip springs for controlled break over in snow.
- Blade floats to clean uneven surfaces.
- Reinforced 21" or 27" high 10-gauge moldboards provide long service life.
- 3/8" x 6" reversible cutting edge of 1044 steel.
- Two clamp-on models for compact tractors.
- Step-through design allows for easy access to skid steer seat.
- Quick hook up on skid steers or front loaders equipped with "Universal" mounting plate.
- Select models integrate either the Euro/Global or John Deere 400/500 series mounting for easier hook up.
- Blade angles right or left.
- Adjustable skid shoes are ½" thick and rotate for longer life.



Adjustable skid shoes are standard



Snow Blades Specifications

For skid steers and tractors with a recommended HP of 40-95 HP.

	SBFL-27108A	SSB-27108A	SBG-27108A	SBJD-27108A	SBFL-2790A	SBS-2790A	SBG-2790A	SBJD-2790A
Overall Width (in/cm)	108 / 274	108 / 274	108 / 274	108 / 274	90 / 229	90 / 229	90 / 229	90 / 229
Overall Height (in/cm)	27 / 69	27 / 69	27 / 69	27 / 69	27 / 69	27 / 69	27 / 69	27 / 69
Moldboard Thickness	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge
Cutting Edge (in/mm) 3/8 x 6 / 9.525 x 152.4	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
5° Lateral Oscillation	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Extension Trip Springs	2	2	2	2	2	2	2	2
Manual Angle Positions	N/A	N/A	N/A	N/A	5	5	5	5
Width @ Full Angle	96 / 244	96 / 244	96 / 244	96 / 244	80 / 203	80 / 203	80 / 203	80 / 203
Tractor Loader Mount	*Brackets Req.	N/A	Euro / Global	400 / 500 JD	*Brackets Req.	N/A	Euro / Global	400 / 500 JD
Skid Steer Mount	N/A	Universal	N/A	N/A	N/A	Universal	N/A	N/A
Adjustable Skid Shoes	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Horse Power Rating	50-95 HP	50-95 HP	50-95 HP	50-95 HP	40-80 HP	40-80 HP	40-80 HP	40-80 HP
Weight (lbs/kg)	748 / 339	735 / 333	717 / 325	765 / 347	660 / 299	646 / 293	630 / 286	675 / 306
Hydraulic Angle Kit	Standard	Standard	Standard	Standard	Optional	Optional	Optional	Optional
Crossover Ref. Valve	Standard	Standard	Standard	Standard	Optional	Optional	Optional	Optional
Optional Top Deflector	360230	360230	360230	360230	360227	360227	360227	360227
Optional Sight Indicator	360235	360235	360235	360235	360235	360235	360235	360235
Product No.	360075	360070	360078	360275	360040	360000	360090	360270

*Optional interfacing quick attach brackets available for most popular models.



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.



Snow Blades Specifications

Models 2160 & 2172 are for skid steers and tractors with a recommended HP of 25-45 HP. SBC clamp-on models are for tractors with a recommended HP up to 35 HP.

	SBFL-2172	SBS-2172	SBC-2172	SBJD-2172	SBFL-2160	SBS-2160	SBC-2160	SBJD-2160
Overall Width (in/cm)	72 / 183	72 / 183	72 / 183	72 / 183	60 / 152	60 / 152	60 / 152	60 / 152
Overall Height (in/cm)	21 / 53	21 / 53	21 / 53	21 / 53	21 / 53	21 / 53	21 / 53	21 / 53
Moldboard Thickness	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge
Cutting Edge (in/mm) 3/8 x 6 / 9.525 x 152.4	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Extension Trip Springs	2	2	2	2	2	2	2	2
Manual Angle Positions	5	5	5	5	5	5	5	5
Width @ Full Angle	62 / 157	62 / 157	62 / 157	62 / 157	52 / 132	52 / 132	52 / 132	52 / 132
Tractor Loader Mount	*Brackets Req.	N/A	Clamp-On	200 / 400 JD	*Brackets Req.	N/A	Clamp-On	200 / 400 JD
Skid Steer Mount	N/A	Universal	N/A	N/A	N/A	Universal	N/A	N/A
Adjustable Skid Shoes	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Horse Power Rating	<45 HP	<45 HP	<35 HP	<45 HP	<45 HP	<45 HP	<35 HP	<45 HP
Weight (lbs/kg)	360 / 163	353 / 160	335 / 152	373 / 169	335 / 152	325 / 147	305 / 138	345 / 156
Hydraulic Angle Kit	Optional	Optional	N/A	Optional	Optional	Optional	N/A	Optional
Crossover Ref. Valve	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Optional Top Deflector	360223	360223	360223	360223	360220	360220	360220	360223
Optional Sight Indicator	360235	360235	360235	360235	360235	360235	360235	360235
Product No.	360160	360130	360290	360225	360140	360100	360280	360250

*Optional interfacing quick attach brackets available for most popular models.



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.



Hydraulic/PTO Concrete Mixers



Worksaver's Skid Steer Mixer, model SS-590 has direct hydraulic drive of the gearbox which eliminates chain and sprocket maintenance resulting in more up-time on the jobsite. Large 11-cubic ft. drum allows the operator to mix, transport and place 5-cubic ft. of concrete. It's efficient design offers the contractor a cost savings over chain driven models.

- All welded steel drum construction with internal paddles for uniform mixing and clean dumping.
- Compact, trouble free, long life design with few moving parts.
- Direct hydraulic drive of the gearbox eliminates chain & sprocket maintenance.
- Flow control valve allows easy control of mixer speed.
- All welded frame "universal" skid steer with step-through design for easy access to the operators' seat.



Model 580 3-pt. mixer is ideal for mixing feed, fertilizer, inoculating seed, potting soil and other mixing jobs.

Hydraulic top link cylinder provides positive dump control. Number 40-roller chain drives mixing drum. Adjustable Cat.I hitch allows easy hook up to most tractors (7/8" dia. lift pins). Sealed ball bearings provide long service life with reduced maintenance.

Concrete Mixer Specifications

	580	SS-590
Capacity	Five (5) cu/ft (1 Bag Mix)	Five (5) cu/ft (1 Bag Mix)
Drum Opening (in/cm)	17.5 / 44	20 / 51
Overall Drum Length (in/cm)	32 / 81	32 / 81
Drum Construction	2-Piece Bolted	Welded Steel
Drive System	Tractor PTO	Hydraulic Direct Thru Gearbox
Hydraulic Requirements	N/A	Minimum 8 GPM
Hitch Requirements	Cat. I (7/8" dia. lift pins)	N/A
Drive Ratio	8.77:1	3.18:1
Flow Control Valve	N/A	Standard
Connect Under Pressure Couplers	N/A	Standard
Parking Stands	Standard	Standard
Shipping Weight (lbs/kg)	253 / 115	395 / 180
Product No.	780620	780950



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.



Power Landscape Rakes


Power Landscape Rakes are the ideal tool for the landscape contractor, large property owner, rental yard, park & recreation department or turf management professional. They do it all, prep, smooth, set grade, level, till, remove rocks and create the perfect seedbed.



- Quick-flip side shields are self-storing on the unit allowing ease of windrowing rocks or debris
- Durable triple sealed bearings with bearing protectors for long service life
- Time saving replaceable rotor bearing assemblies
- Choice of rotors - 2" Sabre Tooth or 1-3/4" Carbide Tooth
- Auto adjust chain tensioner is standard on all models



Carbide Rotor



Sabre Rotor



05-Series Powered Landscape Rakes

Designed for use on Mini / Compact Skid Steers, the hydraulically driven 05-Series offers economy and performance. Standard equipment includes a #60 chain drive, flip-up side shields and single center mounted gauge wheel – all supported by a 3" x 3" x 3/16" all-welded frame. As with all models, these Power Rakes feature an environmentally friendly dry chain case, reducing maintenance costs.

SPECIFICATIONS – 05-Series for Mini Skid Steers with Universal Mount – *Mounts for Kanga available

Model	PXS-305	PXS-405	PXS-305ST	PXS-405ST
Mount Type	Mini-SS	Mini-SS	Mini-SS	Mini-SS
Main Frame (in)	3 x 3 x 3/16			
Overall Width (in/cm)	42/107	56/142	42/107	56/142
Working Width (in/cm)	36/91	48/122	36/91	48/122
Working Depth (in/cm)	0-3.0/0-8	0-3.0/0.8	0-3.0/0.8	0-3.0/0.8
Max. Angle	20° L/R	20° L/R	20° L/R	20° L/R
Hydraulic Angle	N/A	N/A	N/A	N/A
Drive System	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Rotor Drive	#60 Roller Chain	#60 Roller Chain	#60 Roller Chain	#60 Roller Chain
Chain Tensioner	Standard	Standard	Standard	Standard
Rotor Tooth	Carbide	Carbide	2" Sabre	2" Sabre
Gauge Wheel	Single	Single	Single	Single
Flip-up Side Shields	Standard	Standard	Standard	Standard
Material Control Bar	2-position	2-position	2-position	2-position
Weight (lbs/kg)	445/202	481/218	447/203	483/219
Product No.	360500	360505	360510	360520



10-Series Powered Landscape Rakes

Elevating productivity, the 10-Series Power Rakes for Mini / Compact Skid Steers features a #80 chain drive, flip-up side shields, dual gauge wheels, adjustable material bar and optional hydraulic angle.

As with all Power Rakes, bearing protectors and environmentally friendly dry chain case are standard equipment.

SPECIFICATIONS – 10 Series for Mini Skid Steers w/Universal Mount – *Mounts for Bobcat MT & Gehl available

Model	PXS-410	PXS-510	PXS-610	PXS-410ST	PXS-510ST	PXS-610ST
Mount Type	Mini-SS	Mini-SS	Mini-SS	Mini-SS	Mini-SS	Mini-SS
Main Frame (in)	3 x 3 x 3/16					
Overall Width (in/cm)	56/142	68/173	80/203	56/142	68/173	80/203
Working Width (in/cm)	48/122	60/152	72/183	48/122	60/152	72/183
Working Depth (in/cm)	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8
Max. Angle	20° L/R					
Hydraulic Angle	Optional	Optional	Optional	Optional	Optional	Optional
Drive System	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Rotor Drive	#80 Roller Chain					
Chain Tensioner	Standard	Standard	Standard	Standard	Standard	Standard
Rotor Tooth	Carbide	Carbide	Carbide	2" Sabre	2" Sabre	Carbide
Gauge Wheel	Dual	Dual	Dual	Dual	Dual	Dual
Flip-up Side Shields	Standard	Standard	Standard	Standard	Standard	Standard
Material Control Bar	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
Weight (lbs/kg)	524/238	560/254	596/270	526/239	562/255	598/271
Product No.	360600	360605	360610	360615	360620	360625



WARNING: Read and understand the operator's manual before operation. Be sure power unit is properly counterbalanced. Damage to equipment or personal injury could occur.

Choose Worksaver For All Your Land Management



20-Series Powered Landscape Rakes

Responsive and reliable, the 20-Series is designed for Skid Steers up to 65 HP. Features a #80 chain drive, dual flip-up gauge wheels, flip-up side shields and an all-welded frame constructed of 3" x 4" x 1/4" tubing.

Also standard are reliable gauge wheels (16 x 6.50-8) mounted to 4-bolt hubs and a "Flex & Float" System offering the operator flexibility to choose maximum down pressure or float position for site prep.



SPECIFICATIONS – 20-Series for Skid Steers under 65 HP

Model	PSS-620	PSS-720	PSS-620ST	PSS-720ST
Mount Type	Skid Steer	Skid Steer	Skid Steer	Skid Steer
Main Frame (in)	3 x 4 x 1/4			
Overall Width (in/cm)	80/203	92/234	80/203	92/234
Working Width (in/cm)	72/183	84/214	72/183	84/214
Working Depth (in/cm)	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8
Max. Angle	20° L/R	20° L/R	20° L/R	20° L/R
Hydraulic Angle	Optional	Optional	Optional	Optional
Drive System	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Rotor Drive	#80 Roller Chain	#80 Roller Chain	#80 Roller Chain	#80 Roller Chain
Chain Tensioner	Standard	Standard	Standard	Standard
Rotor Tooth	Carbide	Carbide	2" Sabre	2" Sabre
Gauge Wheel	Dual	Dual	Dual	Dual
Flip-up Side Shields	Standard	Standard	Standard	Standard
Material Control Bar	Adjustable	Adjustable	Adjustable	Adjustable
Weight (lbs/kg)	830/376	866/393	832/377	868/394
Product No.	360850	360855	360860	360865

65-Series Powered Landscape Rakes

Consistently delivering high performance, the 65-Series is designed for Skid Steers over 65 HP. It's rugged 4" x 4" x 1/4" frame supports dual flip-up gauge wheels (18.5 x 8.50-8) on 5-bolt hubs, flip-up side shields, adjustable material bar and environmentally dry chain case. A double #80 chain transfers the power to the rotor while chain tensioners of UMHW material provides the correct tension.

SPECIFICATIONS – 65-Series for Skid Steers over 65 HP

Model	PSHD-665	PSHD-765	PSHD-865	PSHD-665ST	PSHD-765ST	PSHD-865ST
Mount Type	Skid Steer					
Main Frame (in)	4 x 4 x 1/4					
Overall Width (in/cm)	80/203	92/234	104/264	80/203	92/234	104/264
Working Width (in/cm)	72/183	84/214	96/244	72/183	84/214	96/244
Working Depth (in/cm)	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8
Max. Angle	20° L/R					
Hydraulic Angle	Optional	Optional	Optional	Optional	Optional	Optional
Drive System	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Rotor Drive	#80 Double Roller Chain					
Chain Tensioner	Standard	Standard	Standard	Standard	Standard	Standard
Rotor Tooth	Carbide	Carbide	Carbide	2" Sabre	2" Sabre	2" Sabre
Gauge Wheel	Dual	Dual	Dual	Dual	Dual	Dual
Flip-up Side Shields	Standard	Standard	Standard	Standard	Standard	Standard
Material Control bar	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
Weight (lbs/kg)	1060/481	1105/501	1145/519	1062/482	1107/502	1147/520
Product No.	360570	360575	360580	360585	360590	360595



WARNING: Read and understand the operator's manual before operation. Be sure power unit is properly counterbalanced. Damage to equipment or personal injury could occur.



25-Series Powered Landscape Rakes

Get more done with a compact tractor when using one of our 25-Series Power Rakes designed for tractors of 24-40 HP. Standard equipment includes a #80 drive chain for dependable power transfer, PTO with slip clutch, dual flip-up gauge wheels, flip-up side shields for easy storage on the machine and adjustable material bar for controlling processed material flow.

SPECIFICATIONS – 25-Series for Tractors 24-40 HP

Model	PTC-525	PTC-625	PTC-725	PTC-525ST	PTC-625ST	PTC-725ST
Mount Type	3-pt Cat. I					
Main Frame (in)	3 x 3 x 3/16					
Overall Width (in/cm)	68/173	80/203	92/234	68/173	80/203	92/234
Working Width (in/cm)	60/152	72/183	84/214	60/152	72/183	84/214
Working Depth (in/cm)	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8
Max. Angle	20° L/R					
Hydraulic Angle	Optional	Optional	Optional	Optional	Optional	Optional
Drive System	PTO	PTO	PTO	PTO	PTO	PTO
Rotor Drive	#80 Roller Chain					
Chain Tensioner	Standard	Standard	Standard	Standard	Standard	Standard
Rotor Tooth	Carbide	Carbide	Carbide	2" Sabre	2" Sabre	2" Sabre
Gauge Wheel	Dual	Dual	Dual	Dual	Dual	Dual
Flip-up Side Shields	Standard	Standard	Standard	Standard	Standard	Standard
Material Control Bar	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
Weight (lbs/kg)	755/343	790/358	825/374	757/343	792/359	827/375
Product No.	360800	360805	360810	360815	360820	360825

40-Series Powered Landscape Rakes

Providing ingenious solutions for your site prep needs, the 40-Series 3-pt mounted Power Rakes are matched to tractors of 35-75 HP. Standard features include PTO with slip clutch for sure power transfer, double #80 chain drive for long service life, rugged 4" x 4" x 1/4" frame, dual flip-up gauge wheel on 5-bolt hubs and heavy-duty adjustable material bar to control processed material flow.



SPECIFICATIONS – 40-Series for Tractors 35-75 HP

Model	PTHD-640	PTHD-740	PTHD-840	PTHD-640ST	PTHD-740ST	PTHD-840ST
Mount Type	3-pt Cat II					
Main Frame	4 x 4 x 1/4					
Overall Width (in/cm)	80/203	92/234	104/264	80/203	92/234	104/264
Working Width (in/cm)	72/183	84/214	96/244	72/183	84/214	96/244
Working Depth (in/cm)	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8
Max. Angle	20° L/R					
Hydraulic Angle	Optional	Optional	Optional	Optional	Optional	Optional
Drive System	PTO	PTO	PTO	PTO	PTO	PTO
Rotor Drive	#80 Double Roller Chain					
Chain Tensioner	Standard	Standard	Standard	Standard	Standard	Standard
Rotor Tooth	Carbide	Carbide	Carbide	2" Sabre	2" Sabre	2" Sabre
Gauge Wheel	Dual	Dual	Dual	Dual	Dual	Dual
Flip-up Side Shields	Standard	Standard	Standard	Standard	Standard	Standard
Material Control Bar	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
Weight (lbs/kg)	1065/483	1160/526	1255/569	1068/484	1162/527	1257/570
Product No.	360870	360875	360880	360885	360890	360895



WARNING: Read and understand the operator's manual before operation. Be sure power unit is properly counterbalanced. Damage to equipment or personal injury could occur.

Choose Worksaver For All Your Land Management



Power Rake Features

Flip-up Gauge Wheels (height adjustable) – Allows accurate control of working depth, keeping machine level for smoother surface finish. Operator can easily move the gauge wheels into the up position for transport on a trailer, reducing the space needed.

Flip-up Side Shields – Operator can easily move the shield out of the way for work where shields are not required. Shields are always with the machine, reducing the chance of misplacement.

Rotor Choice – Available with a carbide aggressor tooth (1-3/4") or 2" Sabre tooth (heat treated alloy material). Sabre tooth offers excellent reliability and performance for general use. Aggressor tooth offers more aggressive tilling action.

Dry Chain Case – Environmentally friendly dry chain case reduces maintenance as there is no oil to contend with. Chain only requires lubrication every 15-20 hours and is simply done by removing the chain case cover.

Heavy-Duty Chain – Chain is #60, #80 or double #80 depending on model. Chain size is matched to the machine for maximum power transfer. Tension is provided by serviceable chain tensioners of UMHW material for longer wear and reliability.

Adjustable Material Bar – Standard on all models for controlling processed material flow. Allows the operator to adjust to soil conditions increasing versatility of the unit.

Triple Seal Rotor Bearing with Replaceable Housing – Bearing housing of ductile material is replaceable, extending the life of the machine. Triple seal bearing keeps dirt out, providing more uptime.

Bearing Protectors – Standard on both sides of bearing on non-drive-end, or on rotor side of bearing on drive-end. Protects bearings from wrapping with material, thus increasing the service life of the bearings.

Lifting Point – Built-in lifting hook is standard on all machines for easier loading / unloading of machine.

Flex & Float System – Skid Steer units feature a "Flex & Float" mount. Allows the operator the flexibility to choose maximum down pressure for preliminary site prep, then switch to float position for final site preparation.





Skid Steer Grader Blade

The patented SSGB-8A Grader is designed to be used by asphalt, landscaping, and concrete flatwork contractors. The unit has a 8-foot, six-way hydraulically controlled moldboard operated by an in-cab remote. With an optional laser system, the grader will maintain grade to tight tolerances. To help prevent damage, the moldboard is shear pin protected. Unit comes complete with 1/2" "connect under pressure" flat-faced hydraulic couplers and a reversible beveled cutting edge for long life. Optional End Plate Kit (Pair, #811980) and Laser Pole Kit (Pair, #812110) available.



Close-up of optional end plate - sold in pairs.



Optional laser pole kit - sold in pairs.

Grader Blades Specifications

	SSGB-8A
Overall Height (in/mm)	46-1/2 / 1181
Overall Length (in/mm)	98 / 2489
Overall Width (in/mm)	95-1/2 / 2426
Weight (lbs/kg)	1195 / 542
Mount Type	Universal Skid Steer
Hydraulic Blade Adjustments	Tilt / Angle / Height
Moldboard Width (in/mm)	95-1/2 / 2426
Moldboard Height (in/mm)	15 / 381 w/Cutting Edge
Moldboard Width, Fully Angled (in/mm)	85 / 2159
Moldboard Rotation Left & Right	25 Degrees
Moldboard Tilt Up or Down	25 Degrees
Reversible Moldboard Cutting Edge (in/mm)	1/2 x 6 / 13 x 152 Double Bevel
Moldboard Shear Pin Protection (in/mm)	5/16 / 8 Diameter Shear Pin (Soft)
3 -Hydraulic Cylinders (in/cm) PSI/bar	2 / 5 Bore x 12 / 30 Stroke 3500 / 241
Flat-Faced Couplers Included (in/cm)	1/2 / 13 Body - Connect Under Pressure
Grader Control Valve	Electric Solenoid Operated
In-Cab Remote Control	Standard
Recommended Min. Skid Steer HP	45 HP (34 kw)
Wheel Bearings	Greaseable Tapered Roller
Tire Size (in/mm)	18-1/2 x 8-1/2 x 8 / 470 x 216 x 203
Product No.	811901

Choose Worksaver For All Your Land Management



Mini Skid Steer Snow Blades

Designed for Mini Skid Steers / Compact Tool Carriers, this 50" snow blade is ideal for clearing sidewalks, eliminating hand shoveling. Incorporating many of the features of our larger snow blades, this blade consistently delivers the performance you demand.

- Two trip springs for controlled breakover in snow
- 3/8" x 6" reversible cutting edge
- Standard Skid Shoes of abrasive resistance steel

Mini Skid Steer Snow Blade Specifications

	SBMS-50	SBMS-50 B/G
Overall Width (in/mm)	50 / 1270	50 / 1270
Overall Height (in/mm)	21 / 533.4	21 / 533.4
Moldboard Thickness	10-gauge	10-gauge
Cutting Edge (in/mm)	3/8 x 6 / 9.525 x 152.4	3/8 x 6 / 9.525 x 152.4
Mount	Universal Mini Skid	Bobcat MT / Gehl*
Weight (lbs/kg)	280 / 127	280 / 127
Product No.	360245	360260

* Note: Also for Bobcat S-70 & Gehl 1640 small cab type units.



Caution — A heavy load can cause your tractor to tip over. When moving heavy loads, keep the load as close to the ground as possible, go slowly around turns, and be sure the front or rear of tractor is properly counterbalanced with weights.

Caution — Operators must read & understand operator's manual, particularly the safety warnings and instructions. **The operator is responsible for safety of themselves and others when operating equipment.**



WORKSAVER, INC. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice.

WORKSAVER, INC. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.



Distributed by:



Worksaver, Inc.

P.O. Box 100, Litchfield, IL 62056-0100

Phone: 217-324-5973 • Fax: 217-324-3356

www.worksaver.com • E-mail: sales@worksaver.com

Designed. Engineered. Remarkable Value.